

Customized Strong Self Adhesive Label/ Strong Self Adhesive Sticker Waterproof

Specifications :

Price	Negotion
Brand Name	OEM
Payment Terms	T/T, L/C, Western Union, etc.
Delivery Detail	7days -10days
Certification:	ISO

Detail Introduction :

Specifications

Detail Introduction

Specifications

Price	
Brand Name	
Model Number	
Place of Origin	Shanghai, China
Min.Order Quantity	
Payment Terms	Credit guarantee, T/T, Western Union, Paypal, Wire Transfer, LC.
Supply Ability	
Delivery Detail	
Packaging Details	

Detail Introduction

With big progress of engineering construction and rigid demand of family cars, automobile industry gets a rapid growing into the 21st century. As a consumable part of automobile, tyre industry gain from it.

Crystal Code provide the top quality tyre special usage labels Tyre Label which have the following characteristics:

1. Face material: Except elaborate images the face must have good impermeability. We recommend the eco-friendly PP materials.
2. Adhesive: Rough tyre surfaces require aggressive immediate adhesion.
3. Liner: High coat weight adhesive brings many challenges in die-cutting, so the liner must be straight, smooth and its tension must be strong enough for stamping.

Crystal Code has abundant experiences in this field, with wide range products and stable good quality Tyre Label.

Product No.	CCTLPET025	CCTLPP060	CCTLSGO
Facestock	White Polyester (PET) 35 g/m ² , 0.025 mm	Gloss white polypropylene film (PP) 45 g/m ² , 0.060 mm	Semi gloss p 98 g/m ² , 0.0
Special Coating	Aluminium barrier foil	0.180mm laminated coating and barrier foil	Aluminium lamin
Adhesive	Special purpose permanent, rubber based adhesive.	Special purpose permanent, rubber based adhesive.	Special purpose perm based adhe
Liner	PE coated white kraft paper 135 g/m ² , 0.145mm	White glassine paper 85 g/m ² , 0.082 mm	PE coated white k 85 g/m ² , 0.0
Color	Gloss White	Gloss White	White
Service Temperature	-20?-70?	-30?-80?	-20?-50?
Application Temperature	-10°C	-10°C	-10°C
Printing	Full Color	Full Color	Full Color
Features	With a high barrier to penetration of components within the rubber substrates	Suitable for Auto labelling	Best storage tempera 30°C
Size	Customized	Customized	Customized







