

Strong Adhesive Rubber Tire Label/ Tyre Sticker Waterproof Eco-Friendly Custom Printing

Specifications :

Place of Origin	Shanghai, China
Payment Terms	Credit guarantee T/T Western Union Paypal Wire Transfer LC

Detail Introduction :

Strong adhesive sticker (Tire Labels)

With big progress of engineering construction and rigid demand of family cars, automobile industry gets a rapid growing into the 21st century. As a consumable part of automobile, tyre industry gain from it.

Crystal Code provide the top quality tyre special usage labels Tyre Label which have the following characteristics:

1. Face material: Except elaborate images the face must have good impermeability. We recommend the eco-friendly PP materials.
2. Adhesive: Rough tyre surfaces require aggressive immediate adhesion.
3. Liner: High coat weight adhesive brings many challenges in die-cutting, so the liner must be straight, smooth and its tension must be strong enough for stamping.

Crystal Code has abundant experiences in this field, with wide range products and stable good quality Tyre Label.

Tire sticker labels

Product No.	CCTLPET025	CCTLPP060	CCTLSG075	CCTLPP060S
Facestock	White Polyester (PET) 35 g/m ² , 0.025 mm	Gloss white polypropylene film (PP) 45 g/m ² , 0.060 mm	Semi gloss paper 98 g/m ² , 0.075mm	Bright silver polypropylene film (PP) 45 g/m ² , 0.060 mm
Special Coating	Aluminium barrier foil	0.180mm laminated coating and barrier foil	Aluminium laminated layer	0.180mm laminated coating and barrier foil
Adhesive	Special purpose permanent, rubber based adhesive.	Special purpose permanent, rubber based adhesive.	Special purpose permanent, rubber based adhesive.	Special purpose permanent, rubber based adhesive.
Liner	PE coated white kraft paper 135 g/m ² , 0.145mm	White glassine paper 85 g/m ² , 0.082 mm	PE coated white kraft paper 85 g/m ² , 0.082mm	PE coated white kraft paper 85 g/m ² , 0.082mm
Color	Gloss White	Gloss White	White	Bright silver

Service Temperature	-20?-70?	-30?-80?	-20?-50?	-30?-80?
Application Temperature	-10°C	-10°C	-10°C	-10°C
Printing	Full Color	Full Color	Full Color	Full Color
Features	With a high barrier to penetration of components within the rubber substrates	Suitable for Auto labelling	Best storage temperature is below 30°C	
Size	Customized	Customized	Customized	Customized

Tire sulfuration labels

Product No.	CCTLS130
Facestock	PETG/PEEK
Facestock thickness	0.13 mm
Liner	Glassine Paper, 0.05mm
Color	Gloss White
Service Temperature	-60?-220?
Features	Suitable for normal barcode printer
Printing	Black
Size	Customized









