

What is Bubble Bag?

Detail Introduction :

Types and Functions of Bubble Bag

Material Properties of Bubble Bag

Bubble Bag's Manufacturing Process

Application Scenario of Bubble Bag

Types and Functions of Bubble Bag

Bubble bags include two categories: one is a single-sided bubble bag, and the other is a double-sided bag

1. Single-sided bubble bag is suitable for protecting products with lightweight
2. The double-sided bubble bag has strong shock resistance and is suitable for large and heavy article packaging.

The bubble bag forms bubbles by the way the film contains air to prevent the product from collisions ensure the protection of the product when it is vibrated. At the same time, it also has the function of insulation. There are also requirements for the manufacturing process of bubble bags. In the production process, the bubble middle layer on the surface of the bubble bag is full of air, so it is light, elastic, so insulation, shockproof and wear-resistant. It is waterproof, moisture-proof, and compression resistant is very helpful in reducing vibration. In selecting materials, try to choose some materials that can with high temperatures; it can better guarantee the safety of product packaging.

Content:

Material properties

Manufacturing process

Application scenario

Advantages and disadvantages

Material Properties of Bubble Bag

The primary material of the bubble bag is PE or PO / PE coextrusion film. PE is used more in China, and the latter is more common in Europe and America. But no matter which kind, it is waterproof, and the seal process is destroyed at one time. At present, it is also a kind of express bag called a mixed bubble bag, which can be made of composite coextrusion film, pearl film, kraft paper, and aluminized film and has good waterproof, shockproof, and extrusion resistance. It is widely used in electronic products, optical disc express, logistics packaging, and transportation.

Bubble Bag's Manufacturing Process

The production of bubble bags is divided into the following steps:

1. Film blowing

Film blowing is made of plastic raw materials 2426h, 7042, and so on. In case of film blowing, recycled semi granular film, and new upgraded material shall be produced according to the order information. Those that must be bright red, dark blue, or antistatic, black masterbatch and antistatic agent can be used. During the whole film blowing process, the thickness and total width of the bubble pad shall be adjusted immediately according to the order information. When the bubble film is produced, the winding operation is automatically stacked into a large roll, generally divided into three lengths: 50m, 100m, and 150m.

2. Packaging and printing of bubble bag

After making explicit like two peas, the paper has just begun to make coated paper, and then print and print the surface raw materials of the antistatic bubble bags. The color check should be carried out in the whole process of packaging and printing to ensure that the contents printed and printed out are precisely the same as the package printed designs of the customers.

3. Manufacturing and packaging of bubble bag

The total width and size of the roll produced are different. For making packaging bags, it can save raw materials without cutting. For example, if you want to have a 50cm * 50cm bubble bag, you can produce it with a bubble cushion roll with a total width of 100cm. It's not easy to make all unnecessary materials. The bubble bag must ensure the deviation correction device for the feeder's upper, lower, left, and right. To ensure that the manufactured goods comply with customs regulations. However, because the interior of the bubble bag must include gas, it must be heat sealed in production, and it must be more accurate in temperature control. Generally, the single and double sides are set at 310-320 degrees, and the two sides are set at different directions. When the equipment is unstable, it is impossible to make a bubble bag that meets the requirements.

4. Quality inspection, packaging, freight logistics

The quality inspection shall be carried out in the processing process, color inspection and packaging inspection. The printing content inspection shall be carried out in the packaging and printing process; The antistatic performance shall be inspected in the film blowing process, and the specifications, models, dimensions and tensile strength of the antistatic bubble bag shall be reviewed in the bag making process. The antistatic bubble bag, after inspection, can be packed into the warehouse and then distributed according to the spacing of customers, express companies, freight logistics, etc.

Application Scenario of Bubble Bag

It is mainly used for the logistics and transportation protection of electronic products, buffer packaging plastic products, metal products, ceramic products, glass products, and other products that need buffer protection. Bubble film is made of high-pressure low-density polyethylene. It is a kind of transparent packaging material widely used at present. It is mainly used for the postal packaging of products. The bag is equipped with shock-absorbing bubble film. There are countless tiny bubbles in the bubble film, light and elastic. It has the functions of sound insulation, shockproof, and scratchproof. It is widely used for shockproof cushioning and protective packaging of electronics, instruments, ceramics, handicrafts, home appliances, self-propelled car stores, kitchens, furniture, hardware tools, glass products, and precision instruments.



The advantages of bubble bags are as follows:

1. The water-soluble speed can be designed and selected, completely dissolved in water, non-toxic, and pollution-free;
2. Strong tensile strength and good tension;
3. High transparency and good luster;
4. High softness and good touch;
5. Good oil and solvent resistance, heat sealing, and printing;
6. Low permeability and good gas resistance;
7. Plastic buttons or self-adhesive bags can be added;
8. Excellent antistatic performance, no dust absorption, etc.
9. It can be degraded by water, air, sunlight, and biodegradation. Usually, it can be decomposed into

substances in about a month.